




# Heater Hose - 80 Series



**PUROSIL**  
Mission Rubber Company



**adelaide  
belt & hose**



## 80 Series Heater Hose

- Single-ply silicone polyester reinforced wall.
- Also available in heavy wall configurations for high pressure applications.
- High burst strength and excellent heat resistance.
- Recommended for temperatures: -65° to +350°F (-53.9°C to +176.6°C).
- Resistant to coolants, cold leaks, cracking, peeling, aging and ozone.
- Aramid configuration available for temperatures up to 500°F (260°C).
- Meets and exceeds all performance and physical characteristics of SAE J20 R3, Class A 4.1.4.
- Available in 25', 50' and 100' cartons, other reel lengths available depending on hose diameter; contact factory.

Part Number	Hose ID		Hose OD		Burst Strength		
	In	mm	In	mm	Actual	SAE J20R3	TMC
80-018	0.19	4.78	0.39	9.86	350	250	125
80-025	0.25	6.35	0.46	11.68	420	250	125
80-031	0.31	7.90	0.52	14.02	482	250	125
80-038	0.38	9.53	0.64	16.13	422	250	125
80-050	0.50	12.70	0.76	19.30	450	250	125
80-062	0.63	15.88	0.93	23.50	300	200	125
80-075	0.75	19.05	1.07	27.18	275	200	125
80-088	0.88	22.23	1.24	31.37	275	175	125
80-100	1.00	25.40	1.38	35.05	200	175	125

**42 Scotland Road, Mile End 5031**

**Phone: 08 8234 1155**

**Fax: 08 8234 2255**

**email: [sales@abhose.com.au](mailto:sales@abhose.com.au)**

**[www.beltandhose.com.au](http://www.beltandhose.com.au)**