

CAMLOCK TYPES



Type A

Male Adaptor to Female BSP Thread



Type B

Female Coupler to Male BSP Thread



Type C

Female Coupler to Hose Tail



Type D

Female Coupler to Female BSP Thread



Type E

Male Adaptor to Hose Tail



Type F

Male Adaptor to Male BSP Thread

CAMLOCK TYPES



Type DP

Male Dust Plug



Type DC & DCL

Female Dust Cap & Locking Cap

Many other combinations available - please ask - some examples -



Male Camlock



CAMLOCK SIZE		MALE O.D.	SEAL SIZE	
IN	MM	MM	I.D.	O.D.
1/2	12.5	24	17	26
3/4	20	32	22	35
1	25	36	27	39
1-1/4	32	45	32	50
1-1/2	38	53	38	56
2	50	63	50	68
2-1/2	63	76	64	79
3	75	91	75	95
4	100	122	102	123
6	150	176	150	180

WAM CAMLOCK MAXIMUM OPERATING PRESSURE (PSI @ 50 C)											
MATERIAL	CODE	1/2"	3/4"	1"	1-1/4"	1-1/2"	2"	2-1/2"	3"	4"	6"
ALUMINIUM	(GP)	150	250	250	250	250	250	150	125	125	75
BRONZE	(BZ)	150	250	250	250	250	250	150	125	125	75
STAINLESS	(SS)	150	250	250	250	250	250	150	125	125	75
POLYPROPYLENE	(PP)	125	125	125	100	100	100		75	50	
NYGLASS	(NG)	125	125	125	100	100	100		75	50	

GASKET TEMPERATURE RANGE (CELCIUS)		
MATERIAL	FROM	TO
BUNA-N	-40	100
NEOPRENE	-50	108
EPDM	-50	135
VITON	-4	260
TEFLON	-40	120

**adelaide
belt & hose**

42 Scotland Road, Mile End 5031
 Phone: 08 8234 1155
 Fax: 08 8234 2255
 email: sales@abhose.com.au
 www.beltandhose.com.au